



# V-SERIES WITH E-P PLUS<sup>®</sup> CONTROL

PROGRAMMING FLEXIBILITY • TWO CAPACITIES • RINSAVE<sup>®</sup> WATER SAVER



30022 VRJ

## HIGHLY PROGRAMMABLE CONTROL FOR EASE OF USE AND FLEXIBILITY



This comprehensive control can hold 30 wash formulas (including 10 pre-programmed for any of the eight industries), which allows the operator advanced flexibility. The E-P Plus owner/operator may manually create or modify formulas, for accurate and proper

washing. The E-P Plus control also features universal temperature control, programmable cooldown, programmable bath soak, and overnight soak. The two-line display notifies the operator of key benchmarks (wash step, time remaining, etc.), which increases productivity and reduces downtime.

## RINSAVE® WATER SAVER FEATURE



The innovative RinSave® Water Saver feature allows a precise G-force to "sling" the wash liquor (including water, chemistry, and soil) out of the goods after a wash step – saving up to 2 rinses per load and fill/rinse time.



Scan to read more about this time, water, and energy saving feature—only available from Milnor!

## SUPERIOR CYLINDER DESIGN



Milnor's superior cylinder design and tall, lifting ribs yield greater wash/rinse quality.

SPECIFICATIONS	30015 VRJ	30022 VRJ
Capacity*-lbs. (kg)	40 (18)	60 (27)
Cylinder diameter-ins. (mm)	30 (762)	30 (762)
Cylinder depth-ins. (mm)	15 (381)	22 (559)
Door Opening-ins. (mm)	15.5 (394)	15.5 (394)
Cylinder volume-cu. Ft. (L)	6.14 (174)	9 (255)
Overall width-ins. (mm)	34.5 (876)	34.5 (876)
Overall depth-ins. (mm)	48.62 (1234)	55.56 (1412)
Overall height-ins. (mm)	57.32 (1455)	57.69 (1466)
Motor-HP (kW)	5 (3.72)	5 (3.72)
Wash Speeds-RPM	38-43	38-43
Distribution Speed-RPM	65	65
Extraction Speeds-RPM	542-663	542-663
Max Extract Speed-RPM	685	685
Extraction G-Force	200	200
Inlet valve-ins. (mm)	0.75 (19)	0.75 (19)
Drain valve-ins. (mm)	3 (76)	3 (76)
Approx net weight-lbs. (kg)	1,078 (489)	1,112 (504)

Specifications and appearance subject to change without notification. Contact the factory for acoustics data.

\*Depending on density and soil content of goods.



Fits through a 3'-0" doorway



NEMA Premium® efficient inverter-driven motor



Safe chemical injection

Printed in the U.S.A.  
© Pellerin Milnor Corporation  
Brochure B22SLI3002/14074



Pellerin Milnor Corporation  
P.O. Box 400, Kenner, LA, 70063-0400 USA  
Phone: 504.712.7656 • 800.469.8780  
Fax: 504.468.3094  
Email: milnorinfo@milnor.com  
www.milnor.com